

SAE 15W-50 Vollsynthetisch

Fully Synthetic High-Performance Engine Oil

State-of-art fully synthetic high-performance engine oil, developed to meet the highest requirements of heavily loaded passenger car engines.

Properties and features

- The special multigrade properties ensure effective lubrication during cold start and under the most severe operating conditions at high temperatures.
- Ensures optimal protection against wear and corrosion.
- High detergency and dispersing power prevent the formation of deposits and thus the cleanliness of the engine is guaranteed.
- Greatly reduced frictional resistance ensures more power and lower fuel consumption.

Application

This fully synthetic engine oil is recommended for use in heavily loaded passenger car engines operating under severe conditions.

Suitable for gasoline and diesel engines without DPF, included those with direct injection, common rail and turbochargers.

Use and oil change intervals according to manufacturer regulations.

Spezifikationen

Performance level:

ACEA A3/B4

MB 229.3

API SN, SM, SL / CF

VW 502 00, 505 00

Typische Kennwerte

Prüfmethode

Dichte bei 15°C	0,850 g/cm ³	ASTM D 1298
Viskosität bei 40°C	120 mm ² /s	ASTM D 445
Viskosität bei 100°C	18,5 mm ² /s	ASTM D 445
Viskositätsindex	173	ASTM D 2270
Viskosität bei -20°C (CCS)	3'000 cP	ASTM D 5293
TBN	10,2 mg KOH/g	ASTM D 2896
Sulphatasche	1,2 Gew.%	ASTM D 874
Flammpunkt (C.O.C.)	230 °C	ASTM D 92
Pour point	-42 °C	ASTM D 97

Bemerkungen

ADR / SDR : Kein Gefahrgut

VeVA-Code : 13 02 08