

SAE 0W-30 OVX

Fully synthetic motor oil for passenger cars with "low SAPS" technology.

High performance, fully synthetic motor oil formulated with the latest additive technology to meet the latest OPEL/Vauxhall specification OV0401547.

The product is specifically designed to prevent and minimize the risk of Low Speed Pre Ignition (LSPI). Therefore, the use of this latest engine oil provides the best possible protection against turbocharger oxidation and deposits in the modern low emission engines.

Properties and features

- Specially formulated to prevent and minimize the risks of Low Speed Pre Ignition (LSPI)
- Low Ash Technology: Keeps the aftertreatment system clean, ensures long aftertreatment system life and reduces particulate emissions.
- Keeps the engine clean and prevents the formation of oil sludge.
- High wear protection, excellent oxidation resistance and optimum shear stability
- Improved "fuel economy" characteristics, better fluidity and behavior at low temperatures.

Use

Fully synthetic engine oil with low ash technology and long life properties for use in modern gasoline and diesel engines. Specially designed for the latest OPEL/Vauxhall aggregates, its high quality performance makes it suitable for a large number of other models of vehicles according to the manufacturer's specifications below.

Observe manufacturer's specifications and instructions before use.

Spezifikationen und Performance

ACEA C2	OPEL OV0401547
API SP RC, SP, SN Plus	MB 229.61
ILSAC GF-6A	FIAT 9.55535-DS1, GS1 - performance

Typische Kennwerte

		Prüfmethode
Dichte bei 15°C	0,845 g/cm ³	ASTM D 1298
Viskosität bei 40°C	48 mm ² /s	ASTM D 445
Viskosität bei 100°C	9.5 mm ² /s	ASTM D 445
Viskositätsindex	187	ASTM D 2270
Viskosität bei -35°C (CCS)	5'700 cP	ASTM D 5293
Viskosität HTHS bei 150°C	3.0 cP	CEC-L-36-A-97
TBN	9.4 mgKOH/g	ASTM D 2896
Sulphatasche	0.77 Gew. %	ASTM D 874
Flammpunkt C.O.C.	220 °C	ASTM D 92
Pour point	-45 °C	ASTM D 97
NOACK-Verdampfungsverlust	10.1 Gew. %	CEC-L-40-A-93

Bemerkungen

ADR / SDR : Kein Gefahrgut

VeVA-Code : 13 02 08