

STOU SAE 10W-30

Multipurpose Super Tractor Oil (STOU)

A high quality, high performance multifunctional lubricating oil that meets a wide range of lubricating oil requirements in agricultural applications.

This multipurpose oil is produced with special additives to meet the most significant specifications for diesel and gasoline engines, transmissions, hydraulic systems and wet brakes in agricultural vehicles and equipment.

Properties

- Multipurpose multifunctional oil.
- Very good thermal and aging stability reduces deposits and extends oil service life.
- Excellent cleaning and dispersing properties keep the engine clean.
- Effective protection against rust and corrosion.
- Excellent anti-wear and extreme pressure properties to reduce component wear even under severe conditions.
- Special frictional properties prevent noise and "stick-slip" of oil-bath clutches and wet brakes.
- Good cold flow for safe starting.

Application

This multipurpose multifunctional oil meets the various lubrication requirements of tractors, agricultural machinery and equipment. Can also be used in construction machinery (subject to manufacturer's instructions).

For use in diesel engines with or without turbocharge, gasoline engines, transmissions (except hypoid), hydraulic systems, hydrostatic drives, hydraulic clutches, wet brakes.

Not suitable for modern car engines.

Follow the manufacturer's instructions when using.

Spezifikationen

Motorenöl:	API CF-4, CE, CF/SF MB 228.1 level, MB 227.1 MIL-L-2104 D, ACEA E2 (CCMC D4)
Getriebeöl:	API GL-4, MIL-L-2105 SAE 80W CATERPILLAR TO-2, ALLISON C-4 ZF TE-ML-06B, 06C, 07B
Hydrauliköl:	HVLP-D, DIN 51524-3, ISO 68
John Deere:	JDM J 27
Ford:	M2C 159-B1/C1, 134 B/C
Massey Ferguson:	CMS M 1145, M 1144, M 1139

Astris

STOU SAE 10W-30**Typische Kennwerte****Prüfmethode**

Dichte bei 15°C	0,875 g/cm ³	ASTM D 1298
Viskosität bei 40°C	68 mm ² /s	ASTM D 445
Viskosität bei 100°C	10,7 mm ² /s	ASTM D 445
Viskositätsindex	145	ASTM D 2270
Viskosität bei -20°C (CCS)	3400 cP	ASTM D 5293
Viskosität bei -25°C (CCS)	6300 cP	ASTM D 5293
TBN	10,2 mgKOH/g	ASTM D 2896
Sulphatasche	1,5 Gew. %	ASTM D 874
Flammpunkt C.O.C.	214 °C	ASTM D 92
Pour point	-33 °C	ASTM D 97

Bemerkungen

ADR / SDR : Kein Gefahrgut

VeVA-Code : 13 02 08