



# Fluid Hydro CHF 11S

## Premium Performance Power Steering and Central Hydraulic Fluid

---

Fluid Hydro CHF 11S is a specially developed synthetic high-performance hydraulic fluid, that can be used in power steering systems, shock absorbers, hydro pneumatic suspensions and other hydraulic systems and controls.

The product is also suitable for use in extreme conditions and maintains its full functionality in application areas from -40°C to over 130°C.

In order not to adversely affect his properties and performance profile this product should not be mixed with other hydraulic oils or brake fluids.

**Observe manufacturer's specifications and instructions before use.**

### Specifications / Performance level

---

DIN 51 524-3 // ISO 7308	FORD WSS-M2C204-A
	MAN M3289
BENTLEY JNV862546F	MB 345.0
BMW 81 22 9 407 758, 82 11 1 468 041, 83 29 0 429 576	OPEL B 040 0070
CHRYSLER MS-11655B	PORSCHE 000 043 203 33
FENDT X 902 011 622	PSA S71 2710
	SAAB 3032 380
	VOLVO 1161529 VW TL 52 146 (G 002 000)
	ZF TE-ML 02K

Technical data	Unit	Method
Color	Green	DIN 10964
Density at 15°C	0.830 g/cm <sup>3</sup>	DIN EN ISO 1298
Viscosity at 40°C	18.7 mm <sup>2</sup> /s	DIN EN ISO 3104
Viscosity at 100°C	6.0 mm <sup>2</sup> /s	DIN EN ISO 3104
Viscosity at -40°C	1'100 mPa*s	DIN EN ISO 3104
Viscosity index	313	DIN ISO 2909
Flash point C.O.C.	160 °C	DIN EN ISO 2592
Pour point	-57 °C	ISO 3016

### Health, safety and environment

---

ADR / SDR : Not dangerous

EU Waste List Code : 13 01 13