

Racing SAE 10W-60

Vollsynth

Fully Synthetic High-Performance Engine Oil

Fully synthetic high-performance engine oil, produced with state-of-the-art technology, developed to satisfy the most extreme demands of heavy-duty passenger car engines.

Properties and features

- The special multi-grade properties ensure effective cold start lubrication, as well as under severe operating conditions at high temperatures.
- Ensures optimum protection against wear and corrosion.
- Thanks to the high detergent and dispersant power, deposits are prevented and the cleanliness of the engine is thereby guaranteed.
- Greatly reduced frictional resistance ensures more power and lower fuel consumption.

Application

HELIOS Racing SAE 10W-60 is generally used in sport and heavy-duty passenger car engines operating under extreme conditions.

Suitable for gasoline and diesel engines, with or without turbo.

Performance level

ACEA A3/B4

API SN, SM, SL / CF

Typische Kennwerte

Prüfmethode

Dichte bei 15°C	0,854 g/cm ³	ASTM D 1298
Viskosität bei 40°C	171,0 mm ² /s	ASTM D 445
Viskosität bei 100°C	23,8 mm ² /s	ASTM D 445
Viskositätsindex	170	ASTM D 2270
Viskosität bei -25°C (CCS)	4'900 cP	ASTM D 5293
TBN	10.8 mg KOH/g	ASTM D 2896
Sulphatasche	1.3 Gew.%	ASTM D 874
Flammpunkt (C.O.C.)	230 °C	ASTM D 92
Pour point	-45 °C	ASTM D 97

Bemerkungen

ADR / SDR : Kein Gefahrgut

VeVA-Code: 13 02 08