

# Synthoplus SSL

## SAE 0W-30

### Fully Synthetic Low- Friction Engine Oil

Fully synthetic high-performance low-viscosity engine oil with reduced HTHS viscosity (High Temperature High Shear) and fuel-saving properties, for use in modern gasoline and diesel engines where ACEA A5/B5 specifications are recommended.

This oil is produced with fully synthetic base oils in combination with state-of-art additives.

#### Properties and features

- Reduced High Temperature High Shear viscosity (HTHS).
- Ensures low friction values, which enable reduced fuel consumption under all driving conditions.
- Outstanding cold flow properties.
- Reliable wear protection at low and high temperatures.
- Low oil consumption.
- Best possible engine cleanliness.

#### Use

Fuel-economy engine oil with reduced HTHS viscosity for gasoline and diesel engines in the modern cars when ACEA A5/B5 specification is recommended.

This product can be used in a wide range of petrol and diesel engines of VOLVO passenger cars. For extended oil change intervals up to 30,000 km. This is a low viscosity oil, it may not be used in all engines.

**Observe manufacturer's specifications and instructions before use.**

#### Spezifikationen und Performance

ACEA A5/B5	API SL
	Volvo 95200377
	Fiat 9.55535-G1 - level

#### Typische Kennwerte

#### Prüfmethode

Dichte bei 15°C	0.848 g/cm <sup>3</sup>	ASTM D 1298
Viskosität bei 40°C	50.0 mm <sup>2</sup> /s	ASTM D 445
Viskosität bei 100°C	9.5 mm <sup>2</sup> /s	ASTM D 445
Viskositätsindex	176	ASTM D 2270
Viskosität bei -35°C (CCS)	5100 cP	ASTM D 5293
Viskosität HTHS bei 150°C	2.95 mPa·s (cP)	CEC-L-36-A-97
TBN	11.2 mgKOH/g	ASTM D 2896
Sulphatasche	1.25 Gew. %	ASTM D 874
Flammpunkt C.O.C.	220 °C	ASTM D 92
Pour point	- 45 °C	ASTM D 97
NOACK-Verdampfungsverlust	12.0 Gew. %	CEC-L-40-A-93

#### Bemerkungen

ADR / SDR : Kein Gefahrgut

VeVA-Code : 13 02 08

