



THETIS series

SAE 0W-16 SN PLUS

High performance synthetic passenger car engine oil

High quality engine oil blended with synthetic base oils and selected additives of the latest technology. Specifically suited for modern hybrid and low emissions vehicles (LEV). Very low viscosity SAE 0W-16 oils are recommended namely by HONDA, TOYOTA and LEXUS for selected gasoline and hybrid engines. This product is specifically designed to minimize the risk of low-speed pre-ignition (LSPI).

Properties and features

- Fuel Economy Oil – FEO
- Efficient wear protection especially during stop & go operations
- Reduces the risk of low-speed pre-ignition failures (LSPI).
- Optimum cold start behaviour
- Enhanced engine cleanliness

Use

This product is especially recommended for modern gasoline and diesel engines, for which a low-viscosity fluid of the class SAE 0W-16 is prescribed.

Observe manufacturer's specifications and instructions before use.

Specifications / Performance level

API SP	ILSAC GF-6
API SN RC (Resource Conserving)	
API SN Plus	

Technical data	Unit	Method
Density at 15°C	0.848 g/cm ³	ASTM D 1298
Viscosity at 40 °C	41 mm ² /s	ASTM D 445
Viscosity at 100 °C	7.4 mm ² /s	ASTM D 445
Viscosity index	170	ASTM D 2270
Viscosity at – 35°C (CCS)	4900 cP	ASTM D 5293
HTHS-viscosity	2.4 mPa·s (cP)	CEC-L-36-A-97
TBN	8.1 mgKOH/g	ASTM D 2896
Flash point C.O.C.	210 °C	ASTM D 92
Pour point	-45 °C	ASTM D 97
NOACK evaporation loss	12 % mass	CEC-L-40-A-93

Health, safety and environment

ADR / SDR : Not dangerous EU Waste List Code : 13 02 08