

2-Takt Competition Synth Universal Vollsynth smokeless

Fully Synthetic, High-Performance Engine Oil for Heavy-Loaded 2-Stroke Engines

This product ensures the highest lubrication level even under extreme operating conditions. It is a fully synthetic, smokeless 2-stroke engine oil with a new composition specially developed for the use in sports and racing.

Properties

- Maximum lubrication safety even in hard racing.
- Effective protection against scarring.
- Reduced ash content and the special synthetic base ensure the best engine cleanliness and prevent the formation of deposits in the combustion chamber even at the high temperatures.
- Significantly reduced exhaust smoke.
- Very good blendability with petrol

Application

Fully synthetic 2-stroke engine oil specially developed for heavy-loaded racing and sports engines. It is recommended for all 2-stroke engines under critical operating conditions. Mixture ratio up to at least 2% oil (1:50).

Specifications

JASO FD	TC-W3
ISO-L-EGD	NMMATC-W3/outboard
API TC Plus	SAE M/F 3

Typical Parameters

		Control Method
Colour	blue	ASTM D 1500
Density at 15°C	0,879 g/cm ³	ASTM D 1298
Viscosity at 40°C	64,3 mm ² /s	ASTM D 445
Viscosity at 100°C	10,3 mm ² /s	ASTM D 445
Viscosity index	147	ASTM D 2270
Sulphate ash	0,10 Gew.%	ASTM D 874
Flashpoint C.O.C.	114 °C	ASTM D 92
Pour point	-48 °C	ASTM D 97

Notes

ADR / SDR : No dangerous cargo VeVA-Code : 13 02 08