



ASTRIS ATF DEXRON VI

Synthetic Automatic Transmission Fluid - with Multi-Vehicle Technology

Synthetic automatic gear oil, based on selected basic oils and additives, for use in modern automatic transmissions, in particular cars of the GM Group (Opel).

This product meets the latest DEXRON-VI specification and covers the requirements of DEXRON-II and DEXRON-III because it is completely downward compatible.

Properties and features

- High service life of the product allows ever longer oil change intervals than DEXRON-IIIH
- Boosts the performance of new and old GM automatic transmissions.
- Superior oxidation and thermal stability prevent sludge and residue form sludge and residue formation.
- Optimum performance and wear protection at all operating temperatures
- Lower viscosity allows an optimum cold start and fuel savings
- Optimum performance and gentle switching for the entire service life of the vehicle

Application

For General Motors automatic transmissions according to DEXRON VI and earlier specifications (DEXRON III and II) because it is completely downward compatible.

NOT suitable for CVT- Continuously Variable Transmissions and DCT - Dual Clutch Transmissions.

Observe manufacturers specifications and instructions before use.

Specifications

Performance level:

DEXRON®-VI <i>exceeds:</i> <i>DEXRON-II D and III</i>	<ul style="list-style-type: none"> • AISIN WARNER AW-1 • FORD M LV FNR5 • HYUNDAI SP-IV, SP-IV RR, SP4-M • HYUNDAI NWS 9638 • HONDA ULTRA II, DW-1, ATF Z-1 • IDEMITSU K17 (Jatco 3100 PL085) • JASO M315 1A-LV, M315 2A • JWS 3324, 3317, 3314, 3309 • KIA DW-1, SP-IV, SP-IV M, IV SP IV RR, NWS 9638 • MAZDA ATF-M III, ATF-M V • MB 236.12, 236.14, 236.41 	<ul style="list-style-type: none"> • MITSUBISHI ATF PA, SP-IV, Diaqueen ATF J3 • NISSAN MATIC J/K/S/W • Renault DPO/AL4, Matic D2 • SUBARU ATF 5AT, AW-1 • SUZUKI 3314, 3317, AW-1 • TOYOTA T-III, T-IV, WS (JWS 3324 for Prius eCVT only) • VW (AUDI) G 055 005, G 055 025, G 055 162, G 055 540, G 060 162 • ZF TE-ML 05L, 09, 11A, 11B, 21L • ZF 8-HP, 9-HP
<ul style="list-style-type: none"> • FORD MERCON® LV 		

Technical data

Technical data	Unit	Method
Colour	Red	
Density at 15°C	0.846 g/cm ³	ASTM D 1298
Viscosity at 40°C	30.3 mm ² /s	ASTM D 445
Viscosity at 100°C	6.0 mm ² /s	ASTM D 445
Viscosity index	148	ASTM D 2270
Brookfield viscosity at -40°C	11'000 cP	ASTM D 2983
Flaming point C.O.C.	206 °C	ASTM D 92
Pour point	- 48 °C	ASTM D 97

Health, safety and environment

ADR / SDR : Not dangerous

EU Waste List Code : 13 02 08