



MAERA series

4T RACING 10W-40 MOTO - Fully Synth (PAO + ESTER)

Fully synthetic high-performance motor oil for 4-stroke motorcycles

Fully synthetic high-performance motor oil for the lubrication of 4-stroke motorcycle engines.

Made of high-quality base oils and additives, this product guarantees very good high-temperature stability and optimum lubrication. Suitable for wet couplings

Properties and features

- Fully synthetic formulation with extremely high oxidation stability.
- Excellent wear protection for the engine and transmission.
- High protection against deposits and black sludge.
- Optimum lubrication at high temperatures.
- Reduced cold-start wear due to the excellent low-temperature properties.
- Suitable for wet couplings

Use

Fully synthetic high-performance lubricant, for use in all type of air or water-cooled 4-stroke motorcycle engines, especially developed to guarantee an optimum lubrication even at high loads.

Observe manufacturer's specifications and instructions before use.

Specifications / Performance level

API SM, SL, SJ, SH, SG
JASO MA 2

Technical data	Unit	Method
Density at 15°C	0,850 g/cm ³	ASTM D 1298
Viscosity at 40 °C	89,9 mm ² /s	ASTM D 445
Viscosity at 100 °C	14,4 mm ² /s	ASTM D 445
Viscosity index	167	ASTM D 2270
TBN	7,8 mgKOH/g	ASTM D 2896
Sulphated ash	0,9 % mass	ASTM D 874
Flash point C.O.C.	210 °C	ASTM D 92
Pour point	-48 °C	ASTM D 97

Health, safety and environment

ADR / SDR : Not dangerous

EU Waste List Code : 13 02 08