

RACING 4T

SAE 10W-60 MOTO

Fully Synthetic Smooth-Running Engine Oil for 4-Stroke Motorcycles

High-performance engine oil, for the lubrication of 4-stroke motorcycle engines. Made from synthetic base components and selected additives, it guarantees high-performance properties and highest protection of the engine under all operating conditions.

Properties and features

- The greatly reduced friction resistance ensures better performance and lower fuel consumption
- Optimum protection against wear and corrosion.
- Safe lubrication of the engine at all operating temperatures.
- The synthetic basic components ensure effective lubrication at cold start as well as under the most difficult operating conditions at high temperatures.
- Due to the high detergent and dispersant properties, deposits are reliably prevented and the cleanliness of the engine is ensured.
- Suitable for wet clutches.

Application

This oil is recommended for the lubrication of 4-stroke motorcycle engines. Particularly suitable for high-performance engines.

Spezifikationen

API SM, SL, SJ, SH, SG
JASO MA 2

Typische Kennwerte

		Prüfmethode
Dichte bei 15°C	0.863 g/cm ³	ASTM D 1298
Viskosität bei 40°C	160 mm ² /s	ASTM D 445
Viscosität bei 100°C	23.2 mm ² /s	ASTM D 445
Viskositätsindex	175	ASTM D 2270
Viskosität bei -25°C (CCS)	4200 cP	ASTM D 5293
TBN	7.8 mgKOH/g	ASTM D 2896
Sulphatasche	0.9 % pds.	ASTM D 874
Flammpunkt C.O.C.	228 °C	ASTM D 92
Pour Point	-45 °C	ASTM D 97

Bemerkungen

ADR / SDR : Kein Gefahrgut

VeVA-Code : 13 02 08