

# RACING 4T

## SAE 10W-50 MOTO

### Fully Synthetic Smooth-Running Engine Oil for 4-Stroke Motorcycles

High-performance engine oil, for the lubrication of 4-stroke motorcycle engines. Made from synthetic base components and selected additives, it guarantees high-performance properties and highest protection of the engine under all operating conditions.

#### Properties and features

- The greatly reduced friction resistance ensures better performance and lower fuel consumption
- Optimum protection against wear and corrosion.
- Safe lubrication of the engine at all operating temperatures.
- The synthetic basic components ensure effective lubrication at cold start as well as under the most difficult operating conditions at high temperatures.
- Due to the high detergent and dispersant properties, deposits are reliably prevented and the cleanliness of the engine is ensured.
- Suitable for wet clutches.

#### Application

This oil is recommended for the lubrication of 4-stroke motorcycle engines. Particularly suitable for high-performance engines.

#### Spezifikationen

API SM, SL, SJ, SH, SG  
JASO MA 2

#### Typische Kennwerte

		Prüfmethode
Dichte bei 15°C	0.859 g/cm <sup>3</sup>	ASTM D 1298
Viskosität bei 40°C	123 mm <sup>2</sup> /s	ASTM D 445
Viskosität bei 100°C	18.2 mm <sup>2</sup> /s	ASTM D 445
Viskositätsindex	165	ASTM D 2270
Viskosität bei -25°C (CCS)	5'000 cP	ASTM D 5293
TBN	7.8 mgKOH/g	ASTM D 2896
Sulphatasche	0.9 % pds.	ASTM D 874
Flammpunkt C.O.C.	230 °C	ASTM D 92
Pour Point	-45 °C	ASTM D 97

#### Bemerkungen

ADR / SDR : Kein Gefahrgut

VeVA-Code : 13 02 08